NETWORK SEEDER GEN 3 LINKAGE SPECS

Specifications	8 row	12 row	14 row	16 row
Overall Width (mm)	1500	2100	2470	2770
Working width (mm)	1200	1750	2100	2400
Weight (dry)	265kg	380kg	430kg	490kg
Variable gearbox	Standard	Standard	Standard	Standard
Crumble Roller Drive	Standard	Standard	Standard	Standard
Neoprene Press Roller Bar	Standard	Standard	Standard	Standard
Smoothing Plates	Standard	Standard	Standard	Standard
Fertiliser box capacity (litres volume)	82	117	139	138
Seed box capacity (litres volume)	76	108	129	146
Disc row spacing (mm)	160	160	160	160
Down Pressure (P/Disc Assembly)	33	32	31	31
Maximum fertiliser rate	0 to 1400 kg/ha	0 to 1400 kg/ha	0 to 1400 kg/ha	0 to 1400 kg/ha
3-Point Linkage	CAT -1&2	CAT-1&2	CAT-1&2	CAT-1&2
Price Ex GST	-	-	-	-
Price Inc GST	-	-	-	-

Specs are subject to change without notice

NETWORK SEEDER GEN 3 TRAILING SPECS

Specifications	8 row	12 row	14 row	16 row
Overall Width (mm)	1820	2420	2790	3090
Working width (mm)	1200	1750	2100	2400
Length	3250	3250	3250	3250
Weight (dry)	391kg	507kg	557kg	617kg
Variable gearbox	Standard	Standard	Standard	Standard
Crumble Roller Drive	Standard	Standard	Standard	Standard
Neoprene Press Roller Bar	Standard	Standard	Standard	Standard
Smoothing Plates	Standard	Standard	Standard	Standard
Fertiliser box capacity (litres volume)	82	117	139	138
Seed box capacity (litres volume)	76	108	129	146
Disc row spacing (mm)	160	160	160	160
Down Pressure (P/Disc Assembly)	49	42	40	39
Maximum fertiliser rate	0 to 1400 kg/ha	0 to 1400 kg/ha	0 to 1400 kg/ha	0 to 1400 kg/ha
Trailing	Trailing	Trailing	Trailing	Trailing
Price Ex GST	-	-	-	-
Price Inc GST	-	-	-	-

Options

- **Large seed/fert box giving 2.5 times the volume capacity of standard**
- **12-volt DC Hydraulic System with Anderson Plug installed**

Specs are subject to change without notice