NETWORK SEEDER SD LINKAGE SPECS

Specifications	8 row	12 row	14 row	16 row
Overall Width (mm)	1550	2150	2450	2750
Working Width (mm)	1200	1800	2100	2400
Dry Weight	656	984	1148	1312
Variable gearbox	Standard	Standard	Standard	Standard
Seeding Rates	2kg to 180kg P/Ha	2kg to 180kg P/Ha	2kg to 180kg P/Ha	2kg to 180kg P/Ha
Down Pressure (P/Disc Assembly)	82kgs Pressure)	82kgs Pressure	82kgs Pressure	82kgs Pressure
Fertiliser box capacity (litres volume)	82	117	139	158
Seed box capacity (litres volume)	76	108	129	146
Disc row spacing (mm)	150	150	150	150
Maximum fertiliser rate	0 to 1400 kg/ha	0 to 1400 kg/ha	0 to 1400 kg/ha	0 to 1400 kg/ha
3 Point Linkage	CAT -1 Or 2	CAT-1 Or 2	CAT-2	CAT-2
Price Ex GST	-	-	-	-
Price Inc GST	-	-	-	-

Standard features included On SD Linkage Seeders

- Press Wheel Assembly

Available Options Not Included In Above Prices

- Harrow Tines
- Bison paddock roller
- Large capacity seed/ fertiliser box giving approx. 2.5 times the standard in volume.

NETWORK SEEDER SD LINKAGE SPECS

Specifications	18 row	20 row	22 row
Overall Width (mm)	3050	3350	3650
Working width (mm)	2700	3000	3300
Weight (dry)	1476kg	1640kg	1800kg
Variable gearbox	Standard	Standard	Standard
Seeding Rates	2kg to 180kg P/Ha	2kg to 180kg P/Ha	2kg to 180kg P/Ha
Maximum fertiliser rate	0 to 1400 kg/ha	0 to 1400 kg/ha	0 to 1400 kg/ha
Down Pressure (P/Disc Assembly)	82kg	82kg	82kg
Single Adjustable Seed & Fertiliser Box Combined Capacity (litres volume)	754	838	921
Disc row spacing (mm)	150	150	150
Linkage	CAT 2-3	CAT 2-3	CAT 2-3
Price Ex GST	-	-	-
Price Inc GST	-	-	-

Standard Features Now Included On SD Linkage Seeders

- Press Wheel Assembly

Available Options Not Included In Above Prices

- Harrow Tines
- Bison paddock roller